info@zealinternational.com sales@zealinternational.com support@zealinternational.com quotation@zealinternational.com sit us at: www.zealinternational.com

Hydraulic Jacks ZI 2062

Standards:

Specification:

Hydraulic Jacks have multipurpose utility, i.e. application of loads while engaged in field investigation, determination of load carrying capacity of piles in the field, tensioning of wires in pre-stressed structures, loading of members of any structure for deformation characteristics etc. The jacks are supplied complete with manually operated pumping units fitted with bourdon tube type load gauge and high-pressure flexible hose pipe. All the jacks have a piston travel of 50 mm and jacks upto 1000 kN capacity are provided with retraction springs.

Note: Piston Travel upto 150 mm can be provided on request

Capicity (kN)	Model No.	Specs of Load Gauge		General Specs	
		Range (kN)	L.C. (kN)	Piston Dia. (mm)	Piston Stroke (mm)
50	ZI 2062A	50	0.2	50.0	50
100	ZI 2062B	100	0.5	78.7	50
250	ZI 2062C	250	1	78.7	50
500	ZI 2062D	500	2	111.2	50
1000	ZI 2062E	1000	5	157.0	50
2000	ZI 2062F	2000	10	222.2	50
3000	ZI 2062G	3000	10	272.2	50

