



ZEAL INTERNATIONAL (An ISO 9001 Certified Company)

Head Office: 1, Netaji Subhash Marg Daryaganj, New Delhi - 110002 INDIA

Phone: +91-11-23276114, 23244474, 23250281, 23278846 Fax: +91-11-43580558

Branch Office: 4/20 Kirti Nagar Industrial Area New Delhi - 110015 Phone: +91 11 45380800

Warehouse: 4/26 Kirti Nagar Industrial Area New Delhi - 110015

info@zealinternational.com

sales@zealinternational.com

support@zealinternational.com

quotation@zealinternational.com

Visit us at: www.zealinternational.com

Relative Density Test ZI 3040

Standards: IS 2720 (PART XIV), ASTM D 4253 & ASTM D 4254

Specification:

The equipment consists one each of: Vibratory table, with a cushioned steel vibrating decks about 75cm x 75cm. It has a frequency of approximately 3600 vibratory table, minute under a 11.5kg load. Amplitude is variable in between 0.65mm in step of 0.05 to 0.25mm, 0.25 to 0.45 mm and 0.45 to 0.65mm. Suitable for operations on 415V, Three Phase supply. Cylindrical metal unit weight mould, 3000ml capacity. Guide sleeve with clamp assembly. Surcharge base plate for mould. Handle for surcharge base plate. Surcharge weight. The total weight together with surcharge base plate and handle is equipment to 140 kg. / cm². For mould. Cylindrical metal unit weight mould 15000 ml. capacity. (Total weight together with the above mould & surcharge weight is equivalent to 140 kg./ cm²) dial gauge 0.01mm x 50mm travel. Extension piece 25mm for dial gauge.

