



ZEAL INTERNATIONAL (An ISO 9001 Certified Company)

Head Office: 1, Netaji Subhash Marg Daryaganj, New Delhi - 110002 INDIA

Phone: +91-11-23276114, 23244474, 23250281, 23278846 Fax: +91-11-43580558

Branch Office: 4/20 Kirti Nagar Industrial Area New Delhi - 110015 Phone: +91 11 45380800

Warehouse: 4/26 Kirti Nagar Industrial Area New Delhi - 110015

info@zealinternational.com

sales@zealinternational.com

support@zealinternational.com

quotation@zealinternational.com

Visit us at: www.zealinternational.com

3D Land Geophone -HVSR-MASW-Holisurface GEMINI 2 Hz ZI 10008

Standards:

Specification:

Data acquisition board specifications:

- Power supply: through USB port
- Sampling rate: from 20Hz to 8000 Hz
- A/D Sigma-Delta converter resolution: 24 real Bit
- Record time: from 60'' to 30'
- Acquisition channels: No. 3
- S/N ratio at $f_s=1\text{KHz}$: 117 dB
- S/N ratio at $f_s=8\text{KHz}$: 109 dB
- Passband at $f_s=1\text{KHz}$: 110 Hz, proportional to sampling rate



Gemini-2 Sensors Specifications:

- Nat. Frequency: 2 Hz +/-10%
- Sensibility: 2 V/cm•S-1 +/- 5%
- Internal Resistance: 5.8kO +/-5%
- Damping: 0.7 +/-10%
- Harmonic Distortion: = 0.2%
- Insulating Resistance:= 10 MO
- Working Temp.: from -25°C to + 55°C
- Sensor clamping: automatic when not in use
- Physical Dimensions: diam.128mm, h.175mm
- Weight: 2.15 kg