



ZEAL INTERNATIONAL (An ISO 9001 Certified Company)

Head Office: 1, Netaji Subhash Marg Daryaganj, New Delhi - 110002 INDIA

Phone: +91-11-23276114, 23244474, 23250281, 23278846 Fax: +91-11-43580558

Branch Office: 4/20 Kirti Nagar Industrial Area New Delhi - 110015 Phone: +91 11 45380800

Warehouse: 4/26 Kirti Nagar Industrial Area New Delhi – 110015

info@zealinternational.com

sales@zealinternational.com

support@zealinternational.com

quotation@zealinternational.com

Visit us at: www.zealinternational.com

Cementometer Moisture Meter ZI 2080

Standards:

Specification:

Features & Benefits

- Fast and easy to use; simply insert the prongs into the material being tested
- Accurate
- Completely Portable
- Full range of water cement ratio's Instantaneous readings



The Cementometer represents a break-through in modern moisture measurement technology. By utilizing the latest microwave and microprocessor science, the Cementometer can determine the moisture content of freshly mixed cement, concrete, and mortar. Simply insert the prongs of the probe into the material to be measured and instantaneously the water cement ratio is shown on the easy to read display.

The Cementometer Microwave moisture meter uses a two prong sensor to measure the complex dielectric constant of the material in contact with the prongs. As the dielectric constant of water is four to eight times greater than most aggregates and cements, changes in water content directly effect the sensor output.

An average of five to ten readings is normally taken in order to ensure a valid reading. This output is then converted by the integrated

microprocessor and moisture content is displayed directly.

Two units are available to encompass the full range of water cement ratio's found in wet concrete. The Cementometer Type R handles normal water cement ratio's with its two prong probe. The range of this instrument is approximately 0.35 to 0.65 water/cement. Cementometer Type L™ handles low

water/cement ratio's with its five prong probe. The range of this instrument is approximately 0.25 to 0.5 water cements.

The units come calibrated for standard type I, II, and III cements. It can also be programmed with up to ten different mix design by the user. For highest accuracy, the user should program the unit for the material being used. The Cementometer Type R™ has simple to use calibration process that rapidly creates the user programs without the need for external computing devices. Finally, the Cementometer can store over 150 readings. Storage is complete with the time and date for future reference. Data can be recalled via USB interface to a personal computer running the Cementometer software.